

SPACECRAFT COMPONENTS CORP.

S e r v i n g C o n n e c t o r U s e r s S i n c e 1 9 6 2

micr⁺38999

by



SOURIAU
Connection Technology

Previously the smallest size available.



D38999 Series III (8D) Size 9



#22D
Ø 0.76mm

Compact Shell

Now even SMALLER!





micr⁺38999

Available in Sizes 3, 5 & 7

Contact Size

#26
Ø 0.5mm

Contact Pitch



In three different versions



Bayonet
Coupling



Threaded
Coupling



Quick Disconnect
(Break Away)

50% shorter
33% smaller diameter
3 times lighter
Scoop proof
-55°C to +175°C

THREADED COUPLING 8DA



8DA0*
Square flange
receptacle



8DA1*
In line
receptacle



8DA5*
8DA6*
Plug



8DA7*
Jam nut
receptacle

BREAK AWAY 8BA



8BA1*
In line
receptacle



8BA6*
Plug



8BA7*
Jam nut
receptacle

BAYONET COUPLING 8LTA



8LTA0*
Square flange
receptacle



8LTA1*
In line
receptacle



8LTA2*
Oval flange
receptacle






8LTA6*
Plug




8LTA7*
Jam nut
receptacle

CONTACT LAYOUTS



ORDERING INFORMATION



Highlighted items are carried in stock.

TECHNICAL FEATURES

Mechanical

- **Shell:**
Aluminum alloy (for sizes 3, 5 & 7)
Passivated stainless steel (for sizes 5 & 7)
- **Shell Plating:**
Aluminum:
Zinc nickel (RoHS)
Nickel (RoHS)
Olive drab cadmium
Passivated stainless steel (RoHS)
- **Insulator:** Thermoplastic
- **Contact Body:** Copper alloy
- **Contacts Plating:**
Gold over nickel plated
- **Shell Endurance:**
8BA & 8DA
Aluminum:
500 mating/unmating cycles
Passivated stainless steel:
1000 mating/unmating cycles
8LTA
Aluminum:
250 mating/unmating cycles
Passivated stainless steel:
1000 mating/unmating cycles
- **Vibration:**
8DA
44 grms @ 125°C, 2 axes during 8 hours
8BA & 8LTA
30 grms @ 125°C, 2 axes during 8 hours
- **Shock:**
300g, 3 ms

Electrical

- **Wire Size**

Layout	Wire (AWG)
03-05	24-30
03-35	22-28
05-06	24-30
05-35	22-28
07-09	24-30
07-35	22-28
- **Test Voltage (at sea level):**
Size 22D: 1000 Vrms
Size 26: 400 Vrms
- **Contact Resistance:**
Size 22D: <14.6 mΩ
Size 26: <16 mΩ
- **Contact Rating:**
Size 22D: 5A
Size 26: 3A
- **Contact Retention:**
Size 22D: 45N
Size 26: 30N
- **Shell to Shell Continuity**

	Shell sizes	Aluminum version	Stainless steel version
8BA, 8DA	3, 5 & 7	< 10 mΩ	< 60 mΩ
8LTA		< 250 mΩ	
- **EMI:**
Aluminum: -70dB @ 1GHz
Passivated stainless steel: -55 dB @ 1GHz

Environmental

- **Temperature Range:**
-55°C to + 175°C
- **Water Immersion:**
IP 67 on mated connector
1 meter for 30 min minimum
> IP68 with appropriate cable termination
- **Salt Spray:**
Zinc nickel: 500 hours
Nickel: 48 hours
Olive drab cadmium: 500 hours
Passivated stainless steel: 500 hours

Resistance to fluids

- **According to MIL-DTL-38999 Standard**
Gasoline: JP5 (OTAN F44) Mineral hydraulic fluid: MIL-H-5606 (OTAN H515)
Synthetic hydraulic fluid: Skydrol 500 B4
- **Compatible with de-icing fluids containing potassium acetate**

Non QPL listed.

SPACECRAFT COMPONENTS CORP.

S e r v i n g C o n n e c t o r U s e r s S i n c e 1 9 6 2

SCP 5015 STYLE
CONNECTORS
(CATALOG 101)

SCPT 26482 STYLE
SC1 38999 SERIES I
SC2 38999 SERIES II
SC39 38999 SERIES III
(CATALOG 201)

SCPB SERIES
(CATALOG 302)

CONNECTOR
ACCESSORIES
(CATALOG 401)

**Try our other
connector products.
Catalogs available.**



**SPACECRAFT
COMPONENTS CORP.**

Headquarters

3040 Clayton Street
North Las Vegas, NV 89032

Phone: 702.851.7600
Fax: 702.851.7620

Email: salesinfo@spacecraft.com
Web: www.spacecraft.com

Florida Office

10732 NW 53rd St.
Sunrise, FL 33351
Tel: 954.748.4540
Fax: 954.748.4128

Arizona Office

519 W. Lone Cactus Dr.
Suite 401
Phoenix, AZ 85027
Tel: 623.580.1162
Fax: 623.580.1165

Ohio Office

121 Marrett Farm Rd.
Union, OH 45322
Tel: 937.832.1882
Fax: 888.839.1882

Italy Office

Spacecraft Components, Sp A
Milan, Italy
+39 (335) 719.4512

3P-201
11.10

COMPILED AND PRODUCED BY SPACECRAFT COMPONENTS CORP.
©2010 SPACECRAFT COMPONENTS CORP., NORTH LAS VEGAS, NV 89032